

## Bitumen boiler REKORD 19, 29, and 49



- Powerful small bitumen boiler with propane burner

High-performance small bitumen boilers with removable tub. Heating is by means of a windshielde propane vortex beam burner. Construction and fitting comply with the regulations of the German Bau-Berufsgenossenschaft (construction liability insurance).

With the boiler types 19 and 29 the tub can be easily pulled out and used as a bucket. The equipment of the bitumen boiler 49 includes a lockable hinged lid, lackable drain cook, double jacket insulation and, on request, a dial thermometer for temperature control.

### Technical data REKORD 19:

Content:	approx. 19 l
Bitumen through-put:	40 l/h
Max. propane consumpt.:	approx. max. 0,6 kg/h
Operating pressure:	1,5 bar
Weight:	approx. 13 kg

### Technical data REKORD 29:

Content:	approx. 29 l
Bitumen through-put:	60 l/h
Max. propane consumpt.:	approx. max. 0,8 kg/h
Operating pressure:	1,5 bar
Weight:	approx. 27 kg

## Technical data REKORD 49:

Content:	approx. 49 l
Bitumen through-put:	100 l/h
Max. propane consumpt.:	approx. max. 1,4 kg/h
Operating pressure:	1,5 bar
Weight:	approx. 49 kg

Product	Part No.	Figure
Bitumen boiler REKORD 19 l	0201 0000	 A small, green, cylindrical bitumen boiler with a yellow lid and a single orange hose attached to the side.
Bitumen boiler REKORD 29 l	0202 0000	 A medium-sized, green, cylindrical bitumen boiler with a yellow lid, two handles, and a single orange hose attached to the side.
Bitumen boiler REKORD 49 l	0203 0000	 A large, green, cylindrical bitumen boiler with a yellow lid, two handles, and a single orange hose attached to the side.