

## Disc crack cutter 5060S



With propulsion and hydraulic quick lift

- Environmentally friendly dry crack cutter for low-cost expansion of uneven running stress cracks in road surfaces and for creating expansion joints
- Dry cutting method with dust extraction
- Low deadweight
- Special design makes following "wild cracks" no trouble at all.
- Cutting expansion joints
- Infinitely adjustable depth setting, max. 50 mm with 200 mm cutting disc
- Propulsion makes for easy and effortless work.
- Infinitely adjustable cutting speed

### Technical Details

### Disc crack cutter 5060S

|                                               |           |
|-----------------------------------------------|-----------|
| Item no.                                      | 5360 0000 |
| Drive engine 2-cylinderVanguard petrol engine | 16.9 kW   |
| Length approx.                                | 1270 mm   |
| Width approx.                                 | 670 mm    |
| Height approx.                                | 1370 mm   |
| Deadweight approx.                            | 230 kg    |

### Accessoires

### Diamond cutting disc for asphalt

|                                                     |           |
|-----------------------------------------------------|-----------|
| approx. 150 x 15 x 25.4 mm/cutting width 15/8 mm    | 5068 8200 |
| approx. 200 x 10 x 25.4 mm/cutting width 10 mm      | 5060 8100 |
| approx. 200 x 6 x 25.4 mm/cutting width 6 mm        | 5060 8200 |
| approx. 150 x 30 x 25.4 mm/cutting width 15 mm      | 5060 8300 |
| Protective cover for flush-to-the-wall cutting disc | 5360 1100 |
| Protective cover for 200 mm disc                    | 5360 1003 |
| Brushes for protective cover 150 mm                 | 5360 1002 |
| Brushes for protective cover 200 mm                 | 5360 1004 |
| Wear parts kit                                      | 5360 9900 |