

## EAP VARIANT VA



Stainless steel anchorage point for dowel fixing to steel reinforced concrete ceiling, including rotating eye bolt

The specification text is only available on request.

### Requirements of subsurface:

- reinforced standard concrete (cracked and uncracked) DIN EN 206-1/A2
- Strength class C20/25 to C50/60
- Minimum component thickness 120 mm
- Edge spacing min. 300 mm

### Mounting materials: Mounting kit item no. 48501520

- 4 x anchor bolts M12

### Standards / Approval / Number of users:

- DIN EN 795:2012 Type A for 1 person
- CEN/TS 16415:2013 Type A for 4 people
- DIBt approval Z-14.9-725 for 4 people

| Support height | For roof height | Item no.  |
|----------------|-----------------|-----------|
| 300 mm         | up to 150 mm    | 4850 1300 |
| 400 mm         | up to 250 mm    | 4850 1400 |
| 500 mm         | up to 350 mm    | 4850 1500 |
| 600 mm         | up to 450 mm    | 4850 1600 |
| 700 mm         | up to 550 mm    | 4850 1700 |

Customised support heights up to max. 1000 mm available.

**GRÜN GmbH Spezialmaschinenfabrik**  
Siegener Straße 81 - 83 • 57234 Wilnsdorf-Niederdielfen  
Tel.: +49 (0) 271 - 39 88-0 • Fax: +49 (0) 271 - 39 88-159

[www.gruen-gmbh.de](http://www.gruen-gmbh.de) • [info@gruen-gmbh.de](mailto:info@gruen-gmbh.de)

**GRÜN GmbH Spezialmaschinenfabrik**  
Siegener Straße 81 - 83 • 57234 Wilnsdorf-Niederdielfen  
**Tel.:** +49 (0) 271 - 39 88-0 • **Fax:** +49 (0) 271 - 39 88-159

[www.gruen-gmbh.de](http://www.gruen-gmbh.de) • [info@gruen-gmbh.de](mailto:info@gruen-gmbh.de)