

## GAB 50 / 70 M mastic asphalt finisher



for the automatically installation of mastic asphalt used in road building and hall construction

- The minimum installation width is 2500 mm; can be expanded in steps of 250 mm to a max. of 7500 mm.
- Hydrostatic chain driven all-wheel drive, speed of 0-3 m / min, infinitely adjustable. Can be equipped with rubber or rail wheels. The height is adjusted with stable elevating spindles and is hydraulically driven.
- Finisher tools with milled design with pressing and smoothing surface are propane-heated and each finisher part can be equipped with a thermometer for temperature control.
- The finisher can be equipped with several special equipment:  
Side bulkheads hydraulically adjustable  
Transport frame  
Blade distributor  
Distribution screw  
Road chassis from 20 bis 80 km/h  
Replaceable end fittings

### Technical details:

Description	GAB 50 / 70 M
Installation width	2500 mm – 7500 mm
Height adjustment for finisher section	from +100 mm to -250 mm
Heating for finisher section	Propane gas bar burner made of stainless steel
Drive engine	Hatz diesel engine, type 1D81C, 8 kW, sound-insulated
Traction drive	Hydrostatic all-wheel drive, reversible with rubber wheels
Operating speed:	0.25 to 3.00 m/min
<b>Dimensions of basic unit:</b>	
Approx. length	3050 mm
Approx. width	1650 mm
Approx. height	1700 mm
Installation width	2500 mm
Approx. weight	2800 kg

Subject to technical changes.