

## Mastic asphalt finisher KBR 75 SL



For automatically installation of mastic asphalt for road building with automatic grit

- The minimum installation width is 2500 mm, in steps of 250 mm; the installation width can be increased to a max. of 8500 mm.
- Hydrostatic chain-driven all-wheel drive, speed of 0-3 m / min, infinitely adjustable. Max. moving speed 6 m/min  
Can be equipped with vulcollan wrappings, rail wheels or crawler chassis.  
The height is adjusted with stable elevating spindles and is hydraulically driven.  
Standard hydraulically adjustable side bulkheads
- Finisher tools in milled design with pressing and smoothing surface are propane-heated and each screed part can be equipped with a thermometer for temperature control
- Grit spreading computer-controlled
- There is an option to equip the finisher with various special features:  
Blade distributor  
Distribution screw  
Road chassis from 20 to 80 km/h  
Replaceable end fittings  
Hydraulic pillar chassis  
assembly jig

### Technical details:

Description	KBR 75 SL
Installation width	2500 mm – 8500 mm
Height adjustment finisher section	from +100 mm to -250 mm
Heating for finisher section	Propane gas bar burner made of stainless steel
Drive motor	HATZ diesel engine type 2L41C, 24 kW sound-insulated
Traction drive	Hydrostatic all-wheel drive, reversible with vulcollan wrapping
Operating speed	0.25 – 3.00 m/min
<b>Dimensions of basic unit:</b>	
Approx. length	3250 mm
Approx. width	2450 mm
Approx. height	1900 mm
Approx. installation width	2500 mm

Approx. weight

5800 kg

Subject to technical changes.