

Mastic asphalt recycling boiler 250 l to 800 l



Special equipment for melting and transporting mastic asphalt.

- Boiler capacities 250 to 800 l
- Low deadweight, powerful direct horizontal agitator drive, short melting times and durable inner pan
- Propane gas or fully automatic oil burner heating
(Flame-shield prevents direct flame on the boiler shell by propane gas firing or combustion chamber used for oil firing).
- Device set up on truck or trailer chassis having adequate bearing capacity
- Available in stationary or mobile model

Technical details stationary model:

Description	RGTK 250	RGTK 500	RGTK 800
Item no. RGTK oil	—	82005 0000	82008 0000
Item no. RGTK Gas	82003 0100	82005 0100	82008 0100
Boiler capacity	0.25 m ³	0.5 m ³	0.8 m ³
Approx. length	1860 mm	2350 mm	2600 mm
Approx. width	1200 mm	1200 mm	1200 mm
Approx. height	1530 mm	1480 mm	1480 mm
Filling lid	500 x 600 mm	500 x 1000 mm	500 x 1000 mm
Drain cock	120 mm, round	300 x 200 mm	300 x 200 mm
Approx. deadweight	810 kg	1300 kg	1420 kg

Technical details mobile design:

Description	RGTK 250	RGTK 500	RGTK 800
Item no.	82003 0000	82005 0500	82008 0500
Trailer chassis	Single axle	Tandem	Tandem
Approx. length	3100 mm	4350 mm	4350 mm
Approx. width	1650 mm	1950 mm	1950 mm
Approx. height	1780 mm	1950 mm	2350 mm
Approx. deadweight	1070 kg	2100 kg	2600 kg

Other sizes on request.
Subject to technical changes.