

RVK 200i vertical mobile/stationary



Equipment for melting and processing bituminous joint and rail sealing material.

- Compact design, low weight, quick heat-up time
- High melting power via heat transfer oil with low gas or heating oil consumption
- Hose pre-heating box and safety filling lid are standard features
- Internal sealing unit
- Vertical agitator hydraulically driven
- Single-axle chassis with overrunning and hand brakes
- Height adjustable drawbar
- Devices available with axle friction wheel drive with steering rod or radio remote control
- Lighting and TÜV acceptance, optional DIN coupling ring or ball hitch for cars

Technical details for mobile equipment:

Description	RVK 200i	RVK 200i	RVK 200iS	RVK 200iS
Item no.	0256 0000	0256 0200	0296 0100	0296 0300
Boiler capacity	200 l	200 l	200 l	200 l
Heat transfer oil*	60 l	60 l	60 l	60 l
Diesel motor power	7.5 kW at 3.000/min	7.5 kW at 3.000/min	9.6 kW at 3.000/min	9.6 kW at 3.000/min
Supra Silent Pack	no	no	yes	yes
Pump capacity approx.	up to 17 l/min	up to 17 l/min	up to 17 l/min	up to 17 l/min
High-speed chassis	Single axle	Single axle	Single axle	Single axle
Friction wheel drive	no	no	yes	yes
Approx. length	3.750 mm to 4.000 mm	3.750 mm to 4.000 mm	3.750 mm to 4.000 mm	3.750 mm to 4.000 mm
Approx. width	1.620 mm	1.620 mm	1.620 mm	1.620 mm
Approx. height	1.750 mm	1.750 mm	1.750 mm	1.750 mm
Unloaded weight approx.:	1.070 kg	1.070 kg	1.430 kg	1.430 kg
Perm. total weight	1.450 kg	1.450 kg	1.800 kg	1.800 kg
Heating	Propane	Heating oil	Propane	Heating oil

Description	RVK 200iS remote control	RVK 200iS remote control
-------------	--------------------------	--------------------------

Item no.	0296 0400	0296 0500
Boiler capacity	200 l	200 l
Heat transfer oil*	60 l	60 l
Diesel motor power	9.6 kW at 3.000/min	9.6 kW at 3.000/min
Supra Silent Pack	yes	yes
Pump capacity approx.	up to 17 l/min	up to 17 l/min
High-speed chassis	Single axle	Single axle
Friction wheel drive	yes, with remote control	yes, with remote control
Approx. length	3.750 mm bis 4.190 mm	3.750 mm bis 4.190 mm
Approx. width	1.620 mm	1.620 mm
Approx. height	2.250 mm	2.250 mm
Unloaded weight approx.:	1.430 kg	1.430 kg
Perm. total weight	1.800 kg	1.800 kg
Heating	Propane	Heating oil

Technical details for stationary equipment:

Description	RVK 200i	RVK 200i
Item no.	0286 0000	0286 0200
Boiler capacity	200 l	200 l
Heat transfer oil*	60 l	60 l
Diesel motor power	7.5 kW at 3.000/min	7.5 kW at 3.000/min
Supra Silent Pack	no	no
Pump capacity approx.	up to 17 l/min	up to 17 l/min
High-speed chassis	----	----
Approx. length	2.150 mm	2.150 mm
Approx. width	1.550 mm	1.550 mm
Approx. height	1.600 mm	1.600 mm
Unloaded weight approx.:	960 kg	960 kg
Heating	Propane	Heating oil

*Heat transfer oil is not included with the delivery/subject to technical changes!

Accessories:

Description	Part No.
Board compressor for blowing out sealing hose RVK 200i	0256 5600
Board compressor for blowing out sealing hose RVK 200iS	0296 5600
Bottle holder for 11 kg gas bottle (for RVK 200 oil firing)	0248 9500
Heat transfer oil 1 liter (for amount required per unit, see technical specifications)	99989 0401
Hose clamp for sealing hose	83100 8600

Hose systems:

GRÜN GmbH Spezialmaschinenfabrik
Siegener Straße 81 - 83 • 57234 Wilnsdorf-Niederdielfen
Tel.: +49 (0) 271 - 39 88-0 • Fax: +49 (0) 271 - 39 88-159

www.gruen-gmbh.de • info@gruen-gmbh.de

Description	Part No.
24 V electrically heated single-hose system including Sealing lance (5 m length)	0256 9801
Unit equipped to support electrically heated Sealing hose RVK 200i	0256 9500
Unit equipped to support electrically heated Sealing hose RVK 200iS	0296 9500
4 m sealing hose with reel	0259 9812
Sealing lance for above mentioned sealing hose	0259 9850
Sealing lance with rotary handle for the sealing valve	0259 9750

Additional equipment for sealing lances:

Description	Part No.
sealing shoe "Quad.6"	0323 2000
sealing shoe "Quad.4"	0323 2100
6 mm joint filling tube	0327 9010
10 mm joint filling tube	0327 9020