
EAE SAFEX ESE HD



Single stainless steel anchor device for PPE with rotating swivel eye.

Mounting substrate:

- hollow-core concrete (quality at least C45/55, at least 30 mm mirror thickness)

Fixing:

- 4 pieces special stainless steel dowels (included in delivery)

Dimension:

- Ø 16 mm x height, max. overhang roof structure: 300 mm

Approval:

- general building authority approval according to DIBt

Certificate:

- according to EN 795:2012 Type A, CEN/TS 16415:2017

Installation:

- according to enclosed installation instructions

GRÜN GmbH Spezialmaschinenfabrik
Siegener Straße 81 - 83 • 57234 Wilnsdorf-Niederdielfen
Tel.: +49 (0) 271 - 39 88-0 • **Fax:** +49 (0) 271 - 39 88-159

www.gruen-gmbh.de • info@gruen-gmbh.de

Variants:

Article number	Designation	Height
4600SO14HD	GRÜN EAE SAFEX ESE HD 300	300 mm
4600SO17HD	GRÜN EAE SAFEX ESE HD 400	400 mm
46000000HD	GRÜN EAE SAFEX ESE HD 500	500 mm
4600SO60HD	GRÜN EAE SAFEX ESE HD 600	600 mm
4600SO70HD	GRÜN EAE SAFEX ESE HD 700	700 mm

Customised support heights up to max. 1000 mm available.

GRÜN GmbH Spezialmaschinenfabrik
Siegener Straße 81 - 83 • 57234 Wilnsdorf-Niederdielfen
Tel.: +49 (0) 271 - 39 88-0 • **Fax:** +49 (0) 271 - 39 88-159

www.gruen-gmbh.de • info@gruen-gmbh.de