


SAFEX-ESE MULTI



Stainless steel anchorage point for bolting to solid wood ceilings, including rotating eye bolt.

Standards / approvals for the anchorage device:

- EN 795:2012 Typ A for 1 person
- CEN/TS 16415:2013 for 4 persons

“SAFEX-ESE MULTI” anchorage system:

Article number: 60300000
Construction height: 300 mm to 1000 mm (+45 mm thread M16)
Material: Stainless steel A2
Rod: Ø 16 mm
Base plate: 210 mm x 250 mm

Roof structure / substrate material data:

Substrate	Dimensions	
Solid structural timber (min. C24)	Min. thickness 100 mm	EN 338

The substrate must be part of the static base construction. In case of doubt, this should be checked by a structural engineer.

SAFEX-ESE MULTI has been tested and certified according to EN 795:2012 Type A. Both static and dynamic tests were conducted on the relevant original substrate.

SAFEX-ESE MULTI is suitable as a substructure for fixing the intermediate rope holders of the horizontal

anchorage system Greenline ® (rope safety system) according to DIN EN 795 Type C.

GRÜN GmbH Spezialmaschinenfabrik
Siegener Straße 81 - 83 • 57234 Wilnsdorf-Niederdielfen
Tel.: +49 (0) 271 - 39 88-0 • **Fax:** +49 (0) 271 - 39 88-159

www.gruen-gmbh.de • info@gruen-gmbh.de