

Disc crack cutter 5070S



With electric propulsion and hydraulic quick lift

- Environmentally friendly dry crack cutter for low-cost expansion of uneven running stress cracks in road surfaces and for creating expansion joints
- Dry cutting method with dust extraction
- Low deadweight
- Special design makes following “wild cracks” no trouble at all..
- Cutting expansion joints
- Infinitely adjustable depth setting, max. 50 mm with 200 mm cutting disc
- Propulsion makes for easy and effortless work
- Driving speed is infinitely adjustable from 0 to 35 m/min
- Infinitely adjustable cutting speed

Technical details:

Designation	Disc crack cutter 5070S
Item-no.	5360 0100
Engine	2 cylinder Vanguard-V-Twin 27,2 kW
Length approx.	1.250 mm
Width approx.	700 mm
Height approx.	1.380 mm
Cutting depth approx.	25 – 50 mm
Max. cutting width	up to 20 mm
Propulsion speed approx.	0 to 35 m/min
Dead weight approx.	310 kg

Accessories:

Diamond cutting disc for asphalt approx. 200 x 15 x 25,4 mm / cutting width 15/8 mm	Item-no. 5068 0100
--	--------------------

Diamond cutting disc for asphalt approx. 200 x 10 x 25,4 mm / cutting width 10 mm	Item-no. 5060 8100
Diamond cutting disc for asphalt approx. 200 x 6 x 25,4 mm / cutting width 6 mm	Item-no. 5060 8200
Diamond cutting disc for asphalt approx. 200 x 10 x 25,4 mm with 4 countersunk holes for flush to wall cutting	Item-no. 5060 8800
Adapter for flush to wall cutting with 4 countersunk screws	Item-no. 5360 2000
Brush for protective cover for flush-to-the-wall cutting disc 200 mm	Item-no. 5360 2001
Wear parts kit: Poly-V belts, V-belts, oil filter and air filter, Brushes for protective covers, dust filter and bucket for dust extraction	Item-no. 5360 9918