

Dry joint cutter Dicorona 675 Stage V

Art.-Nr. 5390 0000



Especially suitable for cutting connection and expansion joints.

- Extremely manoeuvrable and easy-to-use machine
- Consistently well-suited for dry cutting
- Integrated dust extraction
- Electro-hydraulic blade lift
- Reliable visual contact with the diamond disc when setting up the machine
- High performance machine with 58,4 HP and powerful dust extraction
- 3 cylinder turbo Hatz diesel engine EU Stage V, EPA Tier 4 final, with soot filter
- Tread, steering wheel and traction drive

Delivery **without** cutting disc!

Technical details:

Description	DICORONA 675 Stage V
Part-No.	5390 0000
Engine	3 cyl. turbo Hatz diesel engine Stage V
Traction drive	Adjustable up to approx. 30 m/min.
Blade diameter	350 mm (500 mm)

Maximum cutting depth	approx. 100 mm (170 mm)
Blade rising and lowering	electro hydraulic
Weight	approx. 910 kg
Length	approx. 1.650 mm
Width	approx. 1.200 mm
Height	approx. 1.500 mm

Accessoires:

Diamond cutting disc 350 x 4,3 x 25,4	Part.-No. 5379 8100
Diamond cutting disc 350 x 6,0 x 25,4	Part.-No. 5379 8200
Diamond cutting disc 350 x 8,0 x 25,4	Part.-No. 5379 8500

Subject to technical changes!